

HCTDCUL SPECIALTY OVERHEAD OPERATOR

Ideal for multi-unit residential parking facilities.



PRODUCT HIGHLIGHT

SMOOTH START/STOP

Ensures Low-Maintenance Performance

NOISE-ISOLATING DESIGN

Provides for Exceptionally Smooth and Ultra-Quiet Operation

RELIABLE

BATTERY BACKUP SECURES AND SAFEGUARDS YOUR PROPERTY BY PROVIDING STANDBY POWER WHEN THE POWER IS DOWN.

HEAVY-DUTY COMMERCIAL GEAR-DRIVEN TRANSMISSION PROVIDES UNSURPASSED RELIABILITY.

SMOOTH START/STOP OPERATION AND MID-TRAVEL REVERSAL EXTEND OPERATOR HARDWARE LIFE.

YELLOW ZINC DICHROMATE RAIL FINISH (8,10,12 FT.)/**CLEAR ZINC RAIL FINISH** (14,16 FT.) OFFERS MAXIMUM RUST PROTECTION.

WARRANTY 5 YEARS.

SMART

NOISE ISOLATORS PROVIDE EXCEPTIONALLY SMOOTH AND QUIET PERFORMANCE.

SELECTABLE SPEED CONTROL OPENS UP TO 11" PER SECOND, 25% FASTER THAN INDUSTRY AVERAGE, TO KEEP TRAFFIC FLOWING.

LOW-PROFILE DESIGN INSTALLS EASILY IN TIGHT APPLICATIONS AT ONLY 8" IN HEIGHT.

myQ® TECHNOLOGY ENABLES YOU TO SECURELY CONTROL AND MONITOR YOUR GATE OPERATOR FROM ANYWHERE.*

SAFE AND SECURE

SECURITY+ 2.0® SAFEGUARDS ACCESS WITH AN ENCRYPTED TRI-BAND SIGNAL TO VIRTUALLY ELIMINATE INTERFERENCE AND OFFER EXTENDED RANGE.

POSILOCK® AUTOMATICALLY POWERS THE OPERATOR AND RETURNS THE GATE/DOOR TO THE CLOSED POSITION WHEN PUSHED OFF THE CLOSED LIMIT.

QUICK CLOSE AND ANTI-TAILGATE QUICKLY SECURE THE PROPERTY, PREVENTING UNAUTHORIZED ACCESS.

FIRE DEPARTMENT COMPLIANCE ALLOWS GATE/DOOR TO AUTO-OPEN UPON LOSS OF AC POWER OR BATTERY DEPLETION.

UL® LISTED GATE OPERATORS WITH MONITORED SAFETY ENTRAPMENT PROTECTION DEVICES.

*Cellular data or Wi-Fi® connection required. Test equipment regularly and follow safety instructions.

INCLUDED ACCESSORIES:

MONITORED COMMERCIAL PROTECTOR SYSTEM®

Increases entrapment protection with through-beam infrared sensors with heavy-duty housings and brackets; NEMA 4 rated; max. range: 45 ft.



CPSUN4G

SAFETY ADD-ONS:

MONITORED RETRO-REFLECTIVE PHOTO EYE

Enhanced retro-reflective photo eye now with heater and wider beam, engineered to stay aligned; max. range: 50 ft.



LMRRL

MONITORED THROUGH-BEAM PHOTO EYES

Enhanced through-beam now with wider beam and heater for high performance in most environments; max. range: 90 ft.



LMTBUL

TOTAL SOLUTION ACCESSORIES:

CONNECTED ACCESS PORTAL, HIGH CAPACITY

Cloud-based access control for residential communities.



CAPXL

CONNECTED ACCESS PORTAL, 2-DOOR CONTROLLER

Keypad and proximity reader functionality controls a single-entry access.



CAP2D

HIGH-TRAFFIC DC BARRIER GATE OPERATOR

Provides easy in-and-out access 24 hours a day to keep traffic flowing.



MAT

PLUG-IN LOOP DETECTOR

Identifies vehicles within the gate or door pathway.



LOOPDETL

RED/GREEN TRAFFIC LIGHT

Assures safe entering and exiting by indicating door status.



RGL24LY

MASTERFUL ENGINEERING.

HCTDCUL

SPECIALTY OVERHEAD OPERATOR

MECHANICS



- **24VDC** Continuous-Duty Motor
- **Operator Duty Rating:** High-Cycle, High-Temperature Continuous Duty on 8, 10 and 12 ft. Rails; 600 Cycles on 14 and 16 ft. Rails
- **Wormgear Reduction:** Oil-Bath Gearbox with 28:1 Gear Reducer

POWER



- **120/230V** Single-Phase
- **Accessory Power:** 24VDC 500mA Output
- **Solar-Ready, Ultra-Reliable System:** Delivers Power When and Where You Need It (LMRRUL/LMTBUL Heater Option Not Recommended for Solar Applications)

COMMERCIAL-GRADE DESIGN



- **Chassis:** Constructed with 1/4 in. Gold Zinc-Plated Steel for Rust Prevention
- **Trolley Assembly:** Heavy-Duty 12-Gauge Steel Track with 6 UHMW Rollers
- **UL® Usage Classification:** II, III and IV
- **Weights:**
 - Powerhead = 86 lbs.
 - **Yellow Zinc Dichromate Finish**
 - HCT08—8 ft. Rail = 93 lbs.
 - HCT10—10 ft. Rail = 111 lbs.
 - HCT12—12 ft. Rail = 129 lbs.
 - **Clear Zinc Finish**
 - HCT14—14 ft. Rail = 150 lbs.
 - HCT16—16 ft. Rail = 172 lbs.

TEMPERATURE SPECIFICATIONS



-4°F (-20°C) to 140°F (60°C)

BATTERY BACKUP OPERATION

Battery	Cycles	Standby Time
(2) 7Ah	112	24 Days

(Cycles and Standby Time Based on Stand-Alone System)




RAILS

- HCT08: 121.5"
- HCT10: 145.5"
- HCT12: 169.5"
- HCT14: 193.8"
- HCT16: 217.8"

CAPACITIES

Rated for Overhead Doors or Gates with up to 16 ft. Rail or Weighing up to 1,000 lbs.



GATE TRAVEL SPEED

BI-PART DELAY OFF (DEFAULT) = 8 IN./SEC. OPEN SPEED*

BI-PART DELAY ON (FAST) = 11 IN./SEC. OPEN SPEED*

*Select gate travel speed using the BI-PART DELAY switch and enable a high-speed open option to help flow in high-traffic areas (open speed only).



STANDARD FEATURES.

PRE-MOTION WARNING ALARM

- Activates On-Board Alarm 3 Seconds Prior to Gate Motion

EXTERNAL ALARM RESET BUTTON

- Instantly Resets the Built-In Safety Alarm Siren

MAXIMUM-RUN TIMER

- Protects Against Damage to the Gate and Operator by Limiting the Unit's Run Time to 120 Seconds

DYNAMIC BRAKING SYSTEM

- Adds Substantial Gate Position Control at All Points of Travel



MONITORED SAFETY INPUTS

- 3 Main Board, 3 Expansion Board

SECURITY+ 2.0® ON-BOARD

RADIO RECEIVER

- Tri-Band 310/315/390 MHz Frequency
- Up to 50 Remote Controls (Unlimited with 811LM/813LM)

LED DIAGNOSTIC DISPLAY

- Simplifies Installation and Troubleshooting

PROGRAMMABLE AUXILIARY RELAYS

- Make Adding Additional Features Easy

SUPPORT.



For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information on Gate Operators, Visit LiftMaster.com/UL325Gates

To Find the Right Perimeter Access Solution for You, Visit LiftMaster.com/Solution-Generator



Sales Support: 800.282.6225
Technical Support Center: 800.528.2806
To Order: 800.323.2276

© 2019 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc.

300 Windsor Drive, Oak Brook, IL 60523

LiftMaster.com

UL® and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved.

Wi-Fi® is a registered trademark of Wi-Fi Alliance

LMPAENPGHCTDCU 7/19

LiftMaster
ELITE SERIES®